PRODUCTION AND SALE OF MACHINES FROM THE SIGMA ASSORTMENT

Company "Metal Components Supplier doo" was founded in 2005 as supplier of parts for the company "SIGMA SRL" and other bakery companies and sectors in Italy and Europe.

Since 2008 in our company is made also finished products for the domestic market, according to project documentation, drawings and standards of the company "SIGMA SRL".

Beside the new equipment, we repair also old models of SIGMA equipment

PLANETARY MIXER „CHEF 20/30 ECO“

Model	kW	Weight (kg)	Voltage	Bowl (l)	Bowl dimension (mm)	Mixer dimension (mm)
CHEF 20 ECO	0.75	95	220/1/50	20	315x290	605x735x1180
CHEF 30 ECO	1.1	100	400/3/50	30	350x365	605x735x1180

TECNICAL CHARACTERISTICS

- Electronic variator (inverter)
- Three-phase motor
- Transmission with belt
- Planetary turns 40-160 rpm
- Report tools and planetary turns i = 2.7
- Removable stainless steel grid
- Stailess steel feet
- CE rules

STANDARD EQUIPEMNT

- Spiral
- Blade
- Whisk

OPTIONALS

- Special tensions
- Scraper
- Discounts on bowls and tools

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA

PLANETARY MIXER „CHEF 40/60 ECO“

Model	kW	Weight (kg)	Voltage	Bowl (l)	Bowl dimension (mm)	Mixer dimension (mm)
CHEF 40 ECO	1.5	185	400/3/50	40	400x370	700x910x1355
CHEF 60 ECO	2.2	240	400/3/50	60	450x430	730x985x1490

TECNICAL CHARACTERISTICS

- Electronic variator (inverter)
- Three-phase motor
- Transmission with belt
- Planetary turns 40-160 rpm
- Report tools and planetary turns i = 2.7
- Removable stainless steel grid
- Stailess steel feet
- CE rules

STANDARD EQUIPEMNT

- Spiral
- Blade
- Whisk

OPTIONALS

- Special tensions
- Scraper
- Discounts on bowls and tools

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA

SHEETRS „SFG“

Model	kW	Weight (kg)	Voltage	Carpet dimension (mm)
SFG 500TM	0.55	185	400/3/50	500x1180
SFG 600TM	0.75	232	400/3/50	595x1180

TECNICAL CHARACTERISTICS

- Rolling cylinders ground and polished in hard chrome ø73
- Belts with different speeds
- Universal and reversible scapers
- Max cylinder opening mm 48
- Rising and dismountable arms
- Bored shoulders in anticorodal steel
- Single-phase inverter
- Ce rules

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA

SPIRAL MIXERS „SILVER (SL)“

Model	kW	Weight (kg)	Voltage	Bowl (l)	Max flour (kg)	Min water (l)	Mixer dimension (mm)
SL 50	1.9/2.6	182	400/3/50	67	30	17	545x875x1185
SL 60	1.9/2.6	192	400/3/50	81	35	21	595x900x1185

TECNICAL CHARACTERISTICS

- Two motors: 1 for the 2 speed spiral and 1 for the bowl with inverter
- Stainless steel bowl, spiral and bowl protection
- Bowl jogs button
- Device for manual use
- Bowl protection according to the CE rules
- Electromecanical control panel with 2 timers
- Machine mounted on wheels
- CE rules
- EAC and ETL certification

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA

SCREW ROUNDER „SFERA“

Model	kW	Weight (kg)	Range weight (gr)	Dimension (mm)
PSR SFERA	0.18	70	50/650	400x610x858
PSR SFERA PLUS	0.18	120	50/1800	540x770x1050

TECNICAL CHARACTERISTICS

- Solid and strudy stainless steel structure
- Interchangeable aluminium endless screws (tefloned for delicate pastry dough- on request)
- NSF certified plastic cylinder
- Stainless steel Output Tray
- Easy to clean and maintenance
- CE rules

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA

SPIRAL MIXERS „TAURO R“

Model	Type	kW	Weight (kg)	Bowl (l)	Bowl dimension (mm)	Mixer dimension (mm)	Max flour (kg)	Min water (l)
TAURO 25R 2V	Fixed bowl	1,1	107	32	420x260	420x800x760	16	9
TAURO 35R 2V	Fixed bowl	1,5	118	48	480x300	480x830x760	22	12
TAURO 25RB 2V	Removable bowl	1,1	114	32	420x260	420x800x760	16	9
TAURO 35RB 2V	Removable bowl	1,5	126	48	480x300	480x830x760	22	12

TECNICAL CHARACTERISTICS

- 2 speeds
- Three-phase motor
- Models with removable bowl and head
- Transmission with reducer and chain
- Stainless steel bowl, spural and grid
- Kinematic motion on pre-lubicated ball bearings
- Bowl rotates
- GOST certification
- CE rules

WARRANTY: 1 year

Metal Components Supplier d.o.o.
Kanicova bb – 34000 Kragujevac
+381 (0)34 304 222
office@mcs.rs
mcs.rs

projected by SIGMA